

according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

o-Xylene, 50 ml

CAS No: 95-47-6
Index No: 601-022-00-9
EC No: 202-422-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

1.3. Details of the supplier of the safety data sheet

Seller

Company name: CONATEX-DIDACTIC Lehrmittel GmbH

Street: Im Forstgarten 1
Place: D-66459 Kirkel
Internet: www.conatex.com

Supplier

Company name: Carbolution Chemicals GmbH Street: Im Stadtwald, Gebäude A1.2

Place: D-66123 Saarbrücken

Contact person: Dr. Michael Bauer Telephone: +49 (0)681 302-71232

e-mail: michael.bauer@carbolution-chemicals.de

Internet: www.carbolution-chemicals.de

1.4. Emergency telephone +49 (0)681 302-71232

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: Xn - Harmful, Xi - Irritant

R phrases: Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 3 Acute toxicity: Acute Tox. 4 Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Hazard Statements:

Flammable liquid and vapour.

Harmful if inhaled.

Harmful in contact with skin. Causes skin irritation.

2.2. Label elements

Hazardous components which must be listed on the label

o-xylene



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 2 of 9

Signal word: Warning

Pictograms: GHS02-GHS07





Hazard statements

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: C8H10 Molecular weight: 106,17

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
202-422-2	o-xylene	100 %
95-47-6	Xn - Harmful, Xi - Irritant R10-20/21-38	
601-022-00-9	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 3 of 9

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml				
Print date: 15.04.2015	Product code: 9992000	Page 4 of 9		

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
95-47-6	o-Xylene	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: No data available

Test method

pH-Value: not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

No data available

Softening point:

No data available

Flash point:

31 °C

Flammability

Solid: not applicable Gas: not applicable
Lower explosion limits: 0,9 vol. %
Upper explosion limits: 6,7 vol. %
Ignition temperature: No data available

Auto-ignition temperature



according to Regulation (EC) No 1907/2006

O-XV	/lene	50	ml
U-7	A I C I I C	, 50	

Print date: 15.04.2015 Product code: 9992000 Page 5 of 9

Solid: not applicable
Gas: 464 °C

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: 8,8 hPa

(at 25 °C)

Vapour pressure: 21,3 hPa

(at 37,7 °C)

Density: not determined Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: 3,12

Viscosity / dynamic:

Viscosity / kinematic:

No data available

vapour density:

not determined

Evaporation rate:

not determined

Solvent separation test:

No data available

Solvent content:

No data available

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

Toxicological data are not available.

Acute toxicity

Toxicological data are not available.



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 6 of 9

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
95-47-6	o-xylene					
	dermal	ATE	1100 mg/kg			
	inhalative vapour	ATE	11 mg/l			
	inhalative aerosol	ATE	1,5 mg/l			

Irritation and corrosivity

No data available

Sensitising effects

No data available

Severe effects after repeated or prolonged exposure

No data available

Carcinogenic/mutagenic/toxic effects for reproduction

Due to missing data no statement can be made whether the substance fullfills the criteria of CMR categories 1 or 2. Practical experiences do not give any evidence for CMR activity of categories 1 or 2.

Specific effects in experiment on an animal

No data available

Additional information on tests

This mixture is classified as hazardous according to 1999/45/EC.

Practical experience

Observations relevant to classification

No data available

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity: The classification criteria for this hazard class are not met by definition.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 7 of 9

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures

of laboratory chemicals

Classified as hazardous waste.

Waste disposal number of used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures

of laboratory chemicals

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE

CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances

Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1307
14.2. UN proper shipping name:	XYLENES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1Limited quantity:5 LTransport category:3Hazard No:30

Other applicable information (land transport)

F1

Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number:	UN 1307
14.2. UN proper shipping name:	XYLENES

D/F

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Classification code:F1Limited quantity:5 L

Other applicable information (inland waterways transport)

F1

Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1307
14.2. UN proper shipping name:	XYLENES

14.3. Transport hazard class(es): 3
14.4. Packing group:



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 8 of 9

Hazard label: 3
Special Provisions: 223
Limited quantity: 5 L
EmS: F-E, S-D

Other applicable information (marine transport)

E1

Air transport (ICAO)

14.1. UN number: UN 1307
14.2. UN proper shipping name: XYLENES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3Special Provisions:A3Limited quantity Passenger:10 L

IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

Other applicable information (air transport)

: Y344 E1

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals



according to Regulation (EC) No 1907/2006

o-Xylene, 50 ml

Print date: 15.04.2015 Product code: 9992000 Page 9 of 9

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant R-phrases (Number and full text)

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour. H312 Harmful in contact with skin.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation. H332 Harmful if inhaled.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.